Amendment "C" page 2 of 4 10/020,407

DOCKET NO. 01-299 FETF: 71739

In the Claims:

1-4. (canceled)

calculating a difference between a value of the selected parameter at a target location and that of an identical relative location with respect to the target location for each of the plurality of electronic circuits to generate a distribution of differences;

calculating an absolute value of the distribution of differences;

calculating an average of the absolute value of the distribution of differences to generate a representative value for the residual for the identical relative location; and

performing a lot averaging for each wafer X-Y coordinate so that a new set of best estimates is re-calculated for each X-Y position.

6. (previously amended): A method of detecting variations in a spatially correlated parameter comprising:

measuring a selected parameter of each of a plurality of electronic circuits replicated on a common substrate;

calculating a difference between a value of the selected parameter at a target location and that of an identical relative location with respect to the target location for each of the plurality of electronic circuits to generate a distribution of differences;

calculating an absolute value of the distribution of

Amendment "C" page 3 of 4 10/020,407

DOCKET NO. 01-299 FETF: 71739

differences; and

calculating an average of the absolute value of the distribution of differences to generate a representative value for the residual for the identical relative location wherein the common substrate comprises a plurality of common substrates wherein best estimates for a given X-Y location are identical to those of a corresponding location on another of the plurality of common substrates.

7. (original): The method of Claim 6 further comprising re-ordering the plurality of common substrates in a same order in which they were processed.

8-13. (canceled)